

# FLYTECH

POS

Build Smart Solutions for Tomorrow

## POS 5000



### Application Benefits :

- Multipurpose Embedded PC Box
- RAID Technology to Prevent Data Loss
- Easy Serviceability and Upgradability
- Dual Display, Dual HDD and Dual LAN




Flytech's POS 5000 is a powerful embedded PC Box built from SECC metal and equipped with a powerful Intel Sandy Bridge processor and Rich I/O ports for a full range of peripheral connectivity. A sleek front key-lock door and side ventilation provide added security and optimal airflow. The POS 5000 offers modularized HDD, ODD, Power USB and Power Supply for easy maintenance and upgrade. It supports AMT/vPro for remote management functionality and RAID technology to prevent data loss. The POS 5000 is an excellent embedded PC Box solution for any type of business.


## Features

- Intel Sandy Bridge Processor
- SECC Metal Housing
- Modular Design for Easy Maintenance and Service
- Rich I/O Ports for Various Peripherals
- Dual Display, Dual HDD and Dual LAN
- RAID Technology for Transactions Data Back-up

### Front



### Rear



## Specification

<b>Motherboard</b>	Type	C69
	Processor	Intel Sandy Bridge CPU
	Chipset	Intel PCH Cougar Point 6.1W, Q67 (SATA Generation 2.0/3.0 & RAID 0,1 Available)
	System Memory	2x DDR3 LONG-DIMM up to 16GB, 1066/1333MHz
	Graphic Engine	Intel HD Graphics 2000/3000, integrated in CPU, frequency 850MHz
<b>Storage Device</b>	Hard Drive	2x 3.5" SATA HDD
<b>Expansion</b>	PCI-E Socket (x16)	1x Riser Card (1x PCI x1 slot & 1x PCI-E x16 slot)
<b>External I/O Ports</b>	USB	4x USB2.0, 2x USB2.0 at front (one is hidden)
	Serial Port	5x DB9 (standard RS232 default 0V; 5V/12V by BIOS setting)
	LAN	2x RJ45
	Cash Drawer	1x RJ11
	Parallel Port	1
	VGA	1x DB15
	Display Port	1
	Audio Line-out	1
	Audio Mic-in	1
	24V Power Output	1
	PS/2	1
	Kensington Lock	1
<b>Control / Indicator</b>	Power Switch	1
	PWR LED Indicator	1
	HDD LED Indicator	1
<b>Power</b>	Power Supply	Internal ATX 230W/ 350W (Option)
<b>Communication</b>	Wireless LAN	802.11 b/g/n WLAN card & antenna (Option)
<b>Option</b>	Serial RS232/422/485	1 (PCI Bracket for COM6)
	DVI-D/ COM6/ DC-12V out	DVI-D/ PCI Bracket for COM6/ DC-12V out blind hole reservation
	mSATA SSD	Standard mSATA SSD (full-size miniCARD type)
	Power USB Module	Power USB (1x 24V, 2x 12V, 1x 5V) & 4x Standard USB
	SATA ODD	DVD RW +/-
<b>Certificate</b>	EMC & Safety	FCC Class A, CE Mark, LVD
<b>Environment</b>	Operating Temperature	5°C ~ 35°C (41°F ~ 95°F)
	Storage Temperature	-20°C ~ 55°C (-4°F ~ 131°F)
	Humidity	20% ~ 85% RH non-condensing
<b>Dimension (WxDxH)</b>		270 x 300 x 120 mm (10.6" x 11.8" x 4.7")
<b>Weight</b>		8 kg (17.6 lbs)
<b>OS Supported</b>		Windows XP Professional, Windows XP Embedded, Windows XP Professional for Embedded, POSReady 2009, Windows 7, POSReady 7, Linux

### Taiwan - Headquarters

No.168, Sing-ai Rd., Neihu District,  
Taipei City 11494, Taiwan, R.O.C.  
Tel: 886-2-8791-4988  
Fax: 886-2-8791-4966  
E-mail: sales@flytech.com.tw  
www.flytech.com

### U.S.A. - California

728 Charcot Ave, San Jose,  
CA 95131, U.S.A  
Tel: 1-510-257-5180  
Fax: 1-510-257-5181  
E-mail: sales@flytech.com

### China - Shanghai

3F Building 39, No. 333 Qin Jiang Rd.,  
Shanghai 200233, P.R.China  
Tel: 86-21-5426-1555  
Fax: 86-21-5426-1001  
E-mail: sales@flytech.com.cn  
www.flytech.com.cn

### China - Hong Kong

Room 01, 6/F, Block A, Tonic Industrial  
Centre, 26 Kai Cheung Road, Kowloon  
Bay, Kowloon, Hong Kong.  
Tel: 852-3525-5800  
Fax: 852-2751-7447  
E-mail: sales@flytech.com.hk